

14GN/14PH Tandem Axle Gooseneck

G.V.W.R.	14,000#	AXLES	Two 7,000# EZ Lube w/Electric Brakes
G.A.W.R. (Ea. Axle)	7,000#	SUSPENSION	Multi-Leaf Slipper Spring w/Equalizer
COUPLER	2-5/16" Ball Adj. Pipe, 3" ID Pintle on PH	TIRE	ST235/16 Load Range E
SAFETY CHAINS	3/8" Grd. 70 w/Safety Latch Hook (2 each)	WHEEL	16 x 6 HD White Modular 8 Bolt
JACKS	Dual 12,000# Drop Leg Jacks (Bolted On), Single 12K TW on PH	FLOOR	2" Pine
NECK	10" Channel	LIGHTS	D.O.T. Stop, Tail, Turn & Clearance
TOP RAIL	None	ELEC. PLUG	7-Way RV
FRAME	12", 16# I-Beam	FINISH (Prep)	Steel is Cleaned and Etched to Ensure Smooth, High Bond Paint Adhesion.
CROSSMEMBERS	3" Channel, 18 Inch Centers	FINISH	Painted with High-Solids Supreme Automotive Grade Enamel and Pin-Striped for a Highly Decorative and Protective Finish.
SIDE RAILS	6" Channel w/Rub Rail and Stake Pockets on 24" Centers		

Standard Features

- Safety Chains Attached w/Cold Rolled Eyelets
- Dual Drop Leg Jacks (Single Speed) Bolted on w/Greasable Handle
- Pintle has Single TW Drop Leg Jack
- 102" Overall Width
- Lockable Toolbox Between GN Uprights
- 2 Side Bed Steps
- 3/8" Heavy Duty Rub Rail
- Safety Reflective Marker Tape
- Floor Secured w/Torx Screws
- Cambered EZ Lube Axles
- Complete Break-A-Way System w/Battery & Charger
- Radial Tires on HD Wheels
- Spare Tire Mount
- Modular Sealed Wiring Harness
- Rubber Mounted Sealed Lighting
- 5' Dovetail w/Double Hinged Spring Assist Fold Over Ramps



Dimensions w/Dovetail			
Model	A	B	C
20 + 5	240"	196"	44"
22 + 5	264"	216"	48"
24 + 5	288"	232"	56"
26 + 5	312"	248"	64"
28 + 5	336"	264"	72"

MODEL#	WEIGHT	DESCRIPTION
14GN-20+5	4,825#	102" x 20' + 5' Tandem 14,000# Gooseneck/Pintle
14GN-22+5	5,085#	102" x 22' + 5' Tandem 14,000# Gooseneck/Pintle
14GN-24+5	5,440#	102" x 24' + 5' Tandem 14,000# Gooseneck/Pintle
14GN-26+5	5,795#	102" x 26' + 5' Tandem 14,000# Gooseneck/Pintle
14GN-28+5	6,155#	102" x 28' + 5' Tandem 14,000# Gooseneck/Pintle

OPTIONS

30K Square Adjustable Screw Type Coupler	Low Profile Tool Box 12" x 18" x 36" (Side Mount)
Dual Two Speed Landing Gear Jacks (150K)	Tool Box 18" x 18" x 36" (Side Mount)
Electric Over Hydraulic Brakes (Drums)	L.E.D. Lighting
Torsion Axles	5' Center Pop-Up Dovetail w/5' Fold Up Ramps
Spare Tire (ST235/16 LR-E)	No Dovetail Option
Tire Upgrade (ST235/16 LR-G)	Pintle in Lieu of Gooseneck
Spare Tire Upgrade (ST235/16 LR-G)	