



Challenger

Member of the
natm
NATIONAL ASSOCIATION OF TRAILER MANUFACTURERS



Model 4064A



Model 612CS Shown with additional options

SPECIFICATIONS

Model	4064A	4084A	508CS	510CS	610CS	612CS	612CT	714CT	716CT	816CT	820CT	824CT
Overall Length	8'10"	10'10"	11'8"	13'8"	14'4"	16'4"	16'4"	18'	20'	20'4"	24'4"	28'4"
Overall Height	5'8"	5'9"	7'5"	7'5"	7'5"	7'5"	8'10"	8'10"	8'10"	8'6"	8'6"	8'6"
Overall Width	5'4"	5'4"	6'6"	6'6"	6'6"	7'6"	7'6"	8'6"	8'6"	8'6"	8'6"	8'6"
Interior Length	5'9"	7'9"	8'5"	10'5"	10'5"	12'5"	12'5"	14'5"	16'5"	16'5"	20'5"	24'5"
Interior Height	4'	4'	5'7"	5'7"	5'7"	5'7"	6'8"	6'8"	6'8"	6'8"	6'8"	6'8"
Interior Width	3'9"	3'9"	4'8"	4'8"	5'8"	5'8"	5'8"	6'8"	6'8"	8'	8'	8'
GVWR	1,500	2,000	2,990	2,990	2,990	2,990	7,000	7,000	7,000	7,000	7,000	7,000
*Curb Weight	560	620	840	980	1100	1200	1800	2120	2260	2800	3100	3400
*Payload	940	1380	2150	2010	1890	1790	5200	4880	4740	4200	3900	3600
Door Opening Wth	3'2"	3'2"	4'2"	4'2"	5'2"	5'2"	5'2"	6'2"	6'2"	7'6"	7'6"	7'6"
Door Opening Ht.	3'9"	3'9"	4'10"	4'10"	4'10"	4'10"	5'11"	5'11"	5'11"	5'11"	5'11"	5'11"
Tire Size	4.8 x 12	175-80-D13	205-75-D14	205-75-D14	205-75-D14	205-75-D14	205-75-D15	205-75-D15	205-75-D15	205-75-D15	205-75-D15	205-75-D15
Tire Load Range	B	C	C	C	C	C	C	C	C	C	C	C
Hitch Ball Size	2"	2"	2"	2"	2"	2"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Brakes	No	No	Opt.	Opt.	Opt.	Opt.	4-Wheel	4-Wheel	4-Wheel	4-Wheel	4-Wheel	4-Wheel

*Weights are approximate and will change with optional equipment.

5' & 6' Wide Single Axle Models

Hitch Height Single Axle: 18"
Platform Height Single Axle: 20"

6' & 7' Wide Tandem Axle Models

Hitch Height Tandem Axles: 22"
Platform Height Tandem Axles: 24"

8'5" Wide Models

Hitch Height 8.5 Wide: 18"
Platform Height 8.5 Wide: 19"
Between Wheel Wheels: 81 1/2"

Ben Hur Trailers

5330 Hamilton-Middletown Rd.
Hamilton, OH 45011
Phone: 513-896-9940
Fax: 513-896-4727
www.BenHurTrailers.com

Occasionally it may become necessary to produce Homesteader products with different components than initially specified. All such changes are approved for use by Homesteader in order to maintain the quality standards associated with the Homesteader name. All illustrations and specifications contained in this literature are based on the latest product information at time of publication. We assume no responsibility for any error in type or print reproduction of specifications in this literature. Homesteader reserves the right to make changes in prices, colors, materials, equipment and specifications, and to discontinue models at any time without notice. Check with our Homesteader dealer for more information if you have specific questions.

© 2004 Homesteader, Inc.

Printed in USA

CHALLENGER STANDARD FEATURES

- ◆ Heavy Duty All Steel Frame
- ◆ Wall Studs 24" O.C.
- ◆ Floor Crossmembers 24" O.C.
- ◆ 14" Trailer Rated Tires/15" on Tandem axle models
- ◆ Contemporary Style Steel Wheels
- ◆ Aluminum Fenders (Except 4064A, 4084A)
- ◆ Fender Lights-on Applicable Models
- ◆ Aerodynamic Fiberglass Nosecap
- ◆ Aerodynamic Styling
- ◆ Aluminum Exterior with Baked Enamel Finish
- ◆ Manufacturer 20 Year Limited Warranty Galvalume Roof
- ◆ 3/4" Exterior Grade Plywood Floor
- ◆ Automotive Quality Gaskets and Seals
- ◆ Sealed Tail Lights
- ◆ D.O.T. Lighting
- ◆ Tongue Jack
- ◆ EZ Lube Hub Axles
- ◆ Breakaway Switch w/charger (tandem models)
- ◆ Electric Brakes (tandem models only, both axles)
- ◆ High Tech Roof Sealant
- ◆ Recessed Door Frames
- ◆ Heavy Duty Exterior Trim

Available in 5 Colors:
White, Red, Black, Grey or Beige



POPULAR OPTIONS AVAILABLE

- Side Entry Door ◆ Rear Ramp Door ◆ Caster Wheel for Tongue ◆ Interior Light
- Spare Tire and Wheel ◆ Ladder Racks ◆ Rear Stabilizer Jacks ◆ Front ATP Stoneguard
- Tie Down Rings ◆ Roof Vents ◆ Vee Nose w/Chrome Point ◆ Chrome Corners

See Dealer for More Options

